

CE Series A2L Refrigerants

Evaporator Coil Collection



Contents	Page
Nomenclature.....	2
Features.....	2
Multi-position Coil.....	3



Product improvement is a continuous process at Advanced Distributor Products. Therefore, product specifications are subject to change without notice and without obligation on our part. Please contact your ADP representative or distributor to verify details.

© 2025 by Advanced Distributor Products. All rights reserved.

Nomenclature & Features

Nomenclature

CE	P	36	14	E32	A	R	
Carrier Enterprise							Refrigerant Detection System (Field Configurable) R = RDS Controller & Sensor (Factory Installed) N = Not Included (Field Installed)
Configuration							Metering Device A = Non-bleed HP-A/C TXV (R454B)
Nominal Tonnage							Slab Number

	Cabinet Width/Height
	14: 14.25"
	17: 17.50"
	21: 21.00"
	24: 24.50"

General Features

- Lanced fin design for enhanced heat transfer.
- Coils are air pressure tested at 500 PSI, leak tested with Helium, sealed and then charged with dry air.
- Screw-on expansion valves available as a field installed kit.
- Non-captive refrigerant lines for easier service.
- R-454B, R-32, AC & Heat Pump compatible with Refrigerant Detection System.
- Refrigerant detection sensor bracket factory installed


Common Features (Multi-position Coils)

- Microban® antimicrobial additive inhibits the growth of mold and mildew on the drain pan.
- Patented HydroTEC™ drain pan design for lower water retention.
- Enhanced grommets for secure, tight fit and easy installation.
- Durable packaging with a bar coded label on the box.
- Dual drains on each side for easy installation.
- Foil faced insulation for easy cleaning.
- Distributor "bell" joints for enhanced quality.
- UV light knockouts for easy installation.
- Perfect fit for your furnace to eliminate coil overhang.

Multi-position Coil Features

- Factory Installed TXV

Multiposition Coil



A = Width
 B = Depth
 C = Height (excluding 3/4" top flange)

Supply Opening: (A - 1.5") x (B - 1.5")
 Return Opening: (A - 1.0") x (B - 0.5")

Dimensions

Model #	Width	Depth	Height	Suction	Weight	Plenum	Plenum	Pallet
	[A]	[B]	[C]	Line	(lbs)	Width	Depth	Qty
CEP2414G31A*	14.25"	21.00"	16.50"	3/4"	30	12.75"	19.50"	12
CEP2417G31A*	17.50"	21.00"	16.50"	3/4"	30	16.00"	19.50"	8
CEP3614G34A*	14.25"	21.00"	20.50"	3/4"	45	12.75"	19.50"	6
CEP3617G34A*	17.50"	21.00"	20.50"	3/4"	45	16.00"	19.50"	4
CEP4817G1KA*	17.50"	21.00"	22.50"	7/8"	48	16.00"	19.50"	4
CEP4821G1KA*	21.00"	21.00"	22.50"	7/8"	48	19.50"	19.50"	4
CEP6021G48A*	21.00"	21.00"	27.50"	7/8"	53	19.50"	19.50"	4
CEP6024G48A*	24.50"	21.00"	27.50"	7/8"	53	23.00"	19.50"	4

(1) Multi-Position Coils come with factory installed TXV

Airflow

Model #	Face ¹		Pressure ² (in WC)
	CFM	Velocity	
		(fpm)	
CEP2414G31A*	600	224	0.22
	800	299	0.25
	1000	375	0.29
CEP2417G31A*	600	224	0.18
	800	299	0.20
	1000	375	0.24
CEP3614G34A*	1000	250	0.22
	1200	300	0.29
	1400	350	0.34
CEP3614G34A*	1000	250	0.13
	1200	300	0.17
	1400	350	0.26
CEP4817G1KA*	1200	270	0.27
	1400	315	0.31
	1600	360	0.34
CEP4821G1KA*	1200	270	0.23
	1400	315	0.29
	1600	360	0.34
CEP6021G48A*	1200	208	0.13
	1400	242	0.23
	1600	277	0.26
	2000	346	0.28
CEP6024G48A*	1200	208	0.13
	1400	242	0.23
	1600	277	0.26
	2000	346	0.28

* Represents choice of Refrigerant Detection System

(1) Air pressure drop data is under wet coil conditions.



2140 Lake Park Blvd, Richardson, TX 75080
www.adpnow.com